

Drop-In

Monolithic Amplifier

DC-4 GHz

Product Features

- DC-4 GHz
- Single voltage supply
- Internally matched to 50 ohms
- Unconditionally stable
- Low Performance variation over temperature
- Transient Protected
- Aqueous washable
- Protected By US Patent 6,943,629

Typical Applications

- Cellular/ PCS/ 3G Base Station
- CATV, Cable Modem & DBS
- Fixed Wireless & WLAN
- Microwave Radio & Test Equipment



ERA-4+

CASE STYLE: VV105
PRICE: \$3.85 ea. QTY. (30)



+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

General Description

ERA-4+ (RoHS compliant) is a wideband amplifier offering high dynamic range. It has repeatable performance from lot to lot. It is enclosed in a Micro-X package. ERA-4+ uses Darlington configuration and is fabricated using InGaP HBT technology. Expected MTBF is 170 years at 85°C case temperature.

simplified schematic and pin description



Function	Pin Number	Description
RF IN	1	RF input pin. This pin requires the use of an external DC blocking capacitor chosen for the frequency of operation.
RF-OUT and DC-IN	3	RF output and bias pin. DC voltage is present on this pin; therefore a DC blocking capacitor is necessary for proper operation. An RF choke is needed to feed DC bias without loss of RF signal due to the bias connection, as shown in "Recommended Application Circuit".
GND	2,4	Connections to ground. Use via holes as shown in "Suggested Layout for PCB Design" to reduce ground path inductance for best performance.

Mini-Circuits®
ISO 9001 ISO 14001 AS9100 CERTIFIED

minicircuits.com

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

RF/IF MICROWAVE COMPONENTS

REV. N
M117811
ERA-4+
080516
Page 1 of 4

Electrical Specifications at 25°C and 65mA, unless noted

Parameter	Min.	Typ.	Max.	Units	Cpk	
Frequency Range*	DC		4	GHz		
Gain	f=0.1 GHz	13.7	14.4	15	dB	≥ 1.5
	f=1 GHz		14.2			
	f=2 GHz	12.5	13	13.6		
	f=3 GHz		12			
	f=4 GHz	10.8	11.3	11.7		
Magnitude of Gain Variation versus Temperature (values are negative)	f=0.1 GHz		.003	.006	dB/°C	
	f=1 GHz		.0025	.006		
	f=2 GHz		.0031	.006		
	f=3 GHz		.0042	.008		
	f=4 GHz		.0051	.01		
Input Return Loss	f=0.1 GHz		35		dB	
	f=2 GHz		30			
	f=3 GHz		21			
	f=4 GHz		21			
Output Return Loss	f=0.1 GHz		35		dB	
	f=2 GHz		21			
	f=3 GHz		21			
	f=4 GHz		16			
Reverse Isolation	f=2 GHz	18	23		dB	
Output Power @ 1 dB compression	f=0.1 GHz		17.5		dBm	≥ 1.5
	f=1 GHz	15	17.3			
	f=2 GHz		16.1			
	f=3 GHz		14			
	f=4 GHz		11.7			
Saturated Output Power (at 3dB compression)	f=0.1 GHz		17.8		dBm	
	f=2 GHz		16.5			
Output IP3	f=0.1 GHz	32	36.1		dBm	≥ 1.5
	f=1 GHz	31	35			
	f=2 GHz	27	30.4			
	f=4 GHz		25			
Noise Figure	f=0.1 GHz		4	5	dB	≥ 1.5
	f=1 GHz		4.2	5.2		
	f=2 GHz		4.2	5.2		
	f=4 GHz		4.5	5.5		
Group Delay	f=2 GHz		80		psec	
Recommended Device Operating Current			65		mA	
Device Operating Voltage		4.3	4.6	4.9	V	≥ 1.5
Device Voltage Variation vs. Temperature at 65mA			-2.9		mV/°C	
Device Voltage Variation vs. Current at 25°C			10.4		mV/mA	
Thermal Resistance, junction-to-case ¹			191		°C/W	

*Guaranteed specification DC-4 GHz. Low frequency cut off determined by external coupling capacitors.

Absolute Maximum Ratings

Parameter	Ratings
Operating Temperature*	-45°C to 85°C
Storage Temperature	-65°C to 150°C
Operating Current	85mA
Power Dissipation	451mW
Input Power	20 dBm

Note: Permanent damage may occur if any of these limits are exceeded. These ratings are not intended for continuous normal operation.
¹Case is defined as ground leads.
^{*}Based on typical case temperature rise 5°C above ambient.




P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

Product Marking



Additional Detailed Technical Information

Additional information is available on our web site. To access this information enter the model number on our web site home page.

Performance data, graphs, s-parameter data set (.zip file)

Case Style: VV105

Plastic micro-x, .085 body diameter, lead finish: tin/silver/nickel


Tape & Reel: F20

Suggested Layout for PCB Design: PL-261

Evaluation Board: TB-431-4+

Environmental Ratings: ENV08T2

Recommended Application Circuit



R BIAS	
Vcc	"1%" Res. Values (ohms) for Optimum Biasing
7	38.3
8	52.3
9	66.5
10	80.6
11	95.3
12	115
13	127
14	143
15	158
16	174
17	187
18	205
19	221
20	237

ESD Rating

Human Body Model (HBM): Class 1A (250 v to < 500 v) in accordance with ANSI/ESD STM 5.1 - 2001

Machine Model (MM): Class M1 (< 100 v) in accordance with ANSI/ESD STM 5.2 - 1999

MSL Rating

Moisture Sensitivity: MSL1 in accordance with IPC/JEDECJ-STD-020C

No.	Test Required	Condition	Standard	Quantity
1	Visual Inspection	Low Power Microscope Magnification 40x	MIP-IN-0003 (MCT spec)	45 units
2	Electrical Test	Room Temperature	SCD (MCL spec)	45 units
3	SAM Analysis	Less than 10% growth in term of delamination	J-Std-020C (Jedec Standard)	45 units
4	Moisture Sensitivity Level 1	Bake at 125°C for 24 hours Soak at 85°C/85%RH for 168 hours Reflow 3 cycles at 260°C peak	J-Std-020C (Jedec Standard)	45 units

MSL Test Flow Chart

